

# MPA1 SOLO SDI

3G  
SDI

AES

ANA

WEB UI




The MPA1 range of audio monitors from TSL Products is trusted by operators and engineers worldwide.

The MPA1-SOLO-SDI provides audio and video monitoring of 3G/HD/SD-SDI signals with an intuitive interface and easy to use controls.

Built on years of global broadcast audio expertise, the powerful and intuitive MPA1 Solo SDI presents users with instant 'at-a-glance' notification of all 16 SDI Embedded Audio Channels on its front panel display, as well as those derived from its dedicated AES and Analog inputs.

The unique 'scroll to hear' function allows users to scroll through all available audio channels, either individually or as stereo pairs, whilst the Select feature allows the front panel to display audio level meters, phase metering and video monitoring modes.


As a member of the MPA1 range of audio monitors, the MPA1-SOLO-SDI comes complete with a comprehensive web-page and SNMP support, allowing remote configuration and control.



## FEATURES

- 2 x auto-sensing, SD/HD/3G-SDI (23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz) video inputs.
- De-embedded audio monitoring from video (SD/HD/3G-SDI) with intuitive 'scroll to hear' of all 16 embedded audio channels.
- Video display of SD/HD/3G-SDI sources
- 2 x Balanced Analogue Inputs on XLR connectors
- 1 x AES3id input on BNC
- 1 x Ethernet connection for web-page and SNMP control.
- 1 x front panel USB connector for system updates.
- 2 x Line Level Balanced Analogue Outputs for connection to external loudspeakers. Line level with selectable mute and -20dB.
- 1 x SDI Loop Thru (with selectable 'fixed' or 'follow' modes).
- 1 x HDMI Output.

REAR PANEL




SPECIFICATIONS


|                       |  |                           |   |
|-----------------------|--|---------------------------|---|
| HEIGHT                | 1RU  | POWER                     | 85-264V ~ 50/60Hz, 0.75A – 0.5A Max 30W |
| DIMENSIONS            | 483mm x 45mm x 100mm                       | UNIT CONTROL              | SNMP, Webpage                           |
| WEIGHT                | 1.4 kg                                     | SDI INPUTS                | 3G/HD/SD-SDI (SMPTE 424M, 292M, 259M)   |
| DISPLAY               | Audio Metering                             | AES 3id                   | SMPTE 276M                              |
| AUDIO CHANNELS        | 16   | BALANCED ANALOGUE INPUTS  | >60k Ohms                               |
| SIGNAL TO NOISE RATIO | 72dB (+4dBu input level, THD+N A weighted) | BALANCED ANALOGUE OUTPUTS | Fixed or Variable                       |
| PEAK ACOUSTIC OUTPUT  | 90dB @ 1foot                               | UPGRADES                  | VIA USB                                 |
| FREQUENCY RESPONSE    | 40Hz to 20kHz +/- 1dB                      |                           |   |

WEBPAGE CONTROL AND MONITORING

LIVE VIEW



CONFIGURATION VIEW



ORDERING INFORMATION

| Ordering Code | Description  |
|---------------|--|
| MPA1-SOLO-SDI | Simple 1RU SDI audio monitor: Front panel display with 16 Level Meters, Source Names, Audio Phase and Video confidence display. 2 x 3G/HD/SD SDI Inputs + 1 x AES3id input and 2 x Balanced Analogue inputs. 1 x Balanced Stereo Output, 1 x Re-clocked 3G/HD/SD SDI Output and HDMI Output + 1 Front Panel Headphone Output, Internal Loudspeakers, Internal PSU, Web-interface and SNMP Control. |